

# WATER FOAM MONITOR

## Key Features:

- Stand post mounted type.
- Horizontal 360 & vertical +90 & -45 rotation.
- Hand-wheel for rotation of swivel joint.
- Available in SS or Carbon steel.
- Gun metal swivel joint with ball bearing.
- Coated with anti-corrosive coating for carbon steel.
- 3% to 6% foam induction.
- Can be used with AFFF, ARFFF & Fluro protein foam compound.
- Aqua-foam nozzle with SS/ PVC pick up tube.
- Flanged Inlet 4"-6" or 8".



Sr. No.	Description	Monitor MOC	Nozzle MOC
1	500 GPM @100 PSI with 3" waterways with jet -spray nozzle	Carbon Steel SS Gun Metal	Aluminium Alloy SS Gun Metal
2	625 GPM @100 PSI with 3" waterways with jet -spray nozzle		
3	750 GPM @100 PSI with 3" waterways with jet nozzle		
4	1000 GPM @100 PSI with 4" waterways with jet -spray nozzle		
5	1250 GPM @100 PSI with 4" waterways with jet nozzle		
6	2000 GPM @100 PSI with 6" waterways with jet -spray nozzle		
7	4000 GPM @100 PSI with 8" waterways with jet nozzle		